

STAR : ODDI

DST CTD

Conductivity, Salinity, Depth and Temperature Logger
Small and cost-effective salinity logger, easy to mount.

Easy to mount on subsea gear and ocean moorings for short or long-term studies. Adding Star-Oddi's plastic protective housing offers flexible mounting options and added protection.



Key features

- Smallest CTD logger on the market
- Flexible mounting with protective housing
- Different ranges, high or low conductivity
- Depth sensors for shallow to deep ocean

Required accessories

PC Communication Cable,
SeaStar Windows software
Option: Polyurethane plastic
protective housing, stainless
steel housing.

Various depth/pressure ranges

Choose a calibration range up
to: 100 m, 500 m, 1200 m 2400

Contact Us

Email: sales@star-oddi.com

Phone: +354 533 6060

Star-Oddi Ltd
Skeidaras 12
210 Gardabaer
Iceland

TECHNICAL SPECIFICATIONS

Sensors	Conductivity (salinity), temperature, pressure (depth)
Size (Diameter x Length)	15 mm x 50 mm
Housing Material	Alumina (Ceramic)
Weight (in Air/in Water)	21g/13g
Data Resolution	12 bits
Conductivity Ranges	Choose between: 13 to 63 mS/cm, 13-50 mS/cm, 3-37 mS/cm or 0.3-5 mS/cm
Conductivity Resolution	Range 13-63 mS/cm: 0.02 mS/cm Range 13-50 mS/cm: 0.01 mS/cm Range 3-37 mS/cm: 0.01 mS/cm Range 0.3-5 mS/cm: 0.002 mS/cm
Conductivity Accuracy	Range 13-63 mS/cm: +/-2 mS/cm Range 13-50 mS/cm: +/-1.5 mS/cm Range 3-37 mS/cm: +/-1.5 mS/cm Range 0.3-5 mS/cm: +/-0.3 mS/cm
Salinity Range	Depends on conductivity and temp. range (consult with Star-Oddi)
Salinity Resolution	*Range 13-63 mS/cm: 0.01 PSU Range 13-50 mS/cm: 0.01 PSU Range 3-37 mS/cm: 0.01 PSU Range 0.3-5 mS/cm: 0.0005 PSU
Salinity Accuracy	*Range 13-63 mS/cm: +/-1.5 PSU Range 13-50 mS/cm: +/-1 PSU Range 3-37 mS/cm: +/-1 PSU Range 0.3-5 mS/cm: +/-0.1 PSU
Saltwater Switch	Available upon customer request (DST CTD logic)
Temperature Range	-1°C to +40°C (30°F to 104°F)
Temperature Resolution	0.032°C (0.058°F)
Temperature Accuracy	+/-0.1°C (0.18°F)
Temperature Response Time	Time constant (63%) reached in 20 sec.

Standard Depth Ranges	1m-100m, 5m-500m, 5m-1200m, 10m-2400m
Depth Resolution	0.03% of selected range
Depth Accuracy	+/-0.6% of selected range
Depth Response Time	Immediate
Memory Type	Non-volatile EEPROM
Memory Capacity	87,217 measurements per sensor
Memory Mangement	Custom programming
Sampling Interval	User specified in second(s) minute(s), or hour(s)
Minimum Measuring Interval	1 second
Multiple Intervals Option	Up to 7 different intervals
Data Retention	25 years
Clock	Real time clock. Accuracy +/-1 min/month.
Communications	Communication Box, wirelss transmission when DST sits in the box. Connection to PC: USB cable.
Attachment Hole	0.9 mm (diameter)
Battery Life	4 years**
Replaceable Battery	No

*Based on conductivity full scale accuracy at 24°C.

**For sampling interval of 10 minutes.

Warranty: 12 months.

Specifications may change without notice.